

MATERIAL SAFETY DATA SHEET**PRODUCT: Cyberbond 2610****REVISED DATE: 01/06/2016****PAGE: 1 of 7****SECTION 1: IDENTIFICATION of the MATERIAL and SUPPLIER**

Product Name: Cyanoacrylate blend. **Code:** C41
Other Names: Cyberbond 2610
Product Use: Instant Adhesive.
Supplier: Trimfix Supplies (A.B.N 90 053 151 397)
Address: Unit 5/200 Hamilton Road, New Gisborne, VIC, 3438
Phone: 03 5428 3988 Facsimile: 03 5428 4988
Emergency Telephone Number:
Poisons Information Centre 131 126 (24 hours a day)

SECTION 2: HAZARD IDENTIFICATION cont.**Statement of Hazardous Nature**

This product is classified as: Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to the Australian Dangerous Goods (ADG) Code. However, this is a C1 Combustible Liquid so must be stored and handled as specified in AS 1940 "The storage and handling of flammable and combustible liquids."

Risk Phrases: R36/37/38. Irritating to eyes, respiratory system and skin.

Safety Phrases: S2, S23, S26, S38, S51, S24/25. Keep out of reach of children. Do not breathe vapours. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. In case of insufficient ventilation, wear suitable respiratory equipment. Use only in well ventilated areas. Avoid contact with skin and eyes.

SUSMP Classification: S5

ADG Classification: None allocated. Not a Dangerous Good under the ADG Code.

UN Number: None allocated

**GHS Signal word: WARNING****HAZARD STATEMENT:**

H227: Combustible liquid.

H315: Causes skin irritation.

H320: Causes eye irritation.

H335: May cause respiratory irritation.

PREVENTION

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261: Avoid breathing fumes, mists, vapours or spray.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.



Address: Unit 5/200 Hamilton Road New Gisborne VIC.
Postal: PO Box 98 Gisborne VIC 3437
Facsimile: 03 5428 4988
M.S.D.S INFORMATION: Telephone: 03 5428 3988

MATERIAL SAFETY DATA SHEET

PRODUCT: **Cyberbond 2610**

REVISED DATE: 01/06/2016

PAGE: 2 of 7

SECTION 2: HAZARD IDENTIFICATION cont.

RESPONSE

P312: Call a POISON CENTRE or doctor if you feel unwell.
P362: Take off contaminated clothing and wash before reuse.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313: If skin irritation occurs: Get medical advice.
P337+P313: If eye irritation persists: Get medical advice.
P391: Collect spillage.
P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

STORAGE

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage.
For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Emergency Overview

Physical Description & Colour: Clear liquid.

Odour: Characteristic odour.

Major Health Hazards: irritating to eyes, respiratory system and skin. Bonds on contact – may stick things to skin, or bond fingers together.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.



Address: Unit 5/200 Hamilton Road New Gisborne VIC.
Postal: PO Box 98 Gisborne VIC 3437
Facsimile: 03 5428 4988
M.S.D.S INFORMATION: Telephone: 03 5428 3988

MATERIAL SAFETY DATA SHEET

PRODUCT: Cyberbond 2610

REVISED DATE: 01/06/2016

PAGE: 3 of 7

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc, %	TWA (mg/m3)	STEL (mg/m3)
2-Propenoic acid, 2-cyano-, ethyl ester	7085-85-0	>10	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SECTION 4: FIRST AID MEASURES

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Should fingers stick together apply a solvent such as acetone to contact areas then wash off with water. Do not use solvents near eyes or open wounds.

Eye Contact: In case of eye contact

immediately flush with water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

SECTION 5: FIRE FIGHTING MEASURES

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. This product is classified as a Flammable liquid, category 4 (C1 combustible) liquid. There is little risk of an explosion from this product if commercial quantities are involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. Cool closed, undamaged containers exposed to fire with water spray.

Flash point: 87°C, DIN 51758

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: Flammable liquid, category 4 (C1 combustible)



Address: Unit 5/200 Hamilton Road New Gisborne VIC.
Postal: PO Box 98 Gisborne VIC 3437
Facsimile: 03 5428 4988
M.S.D.S INFORMATION: Telephone: 03 5428 3988

MATERIAL SAFETY DATA SHEET

PRODUCT: Cyberbond 2610

REVISED DATE: 01/06/2016
PAGE: 4 of 7

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

SECTION 7: HANDLING and STORAGE

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Note that this product is combustible and therefore, for Storage, meets the definition of Dangerous Goods in some states. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage. Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m3) STEL (mg/m3)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being handled commercially.

MATERIAL SAFETY DATA SHEET

PRODUCT: Cyberbond 2610

REVISED DATE: 01/06/2016
PAGE: 5 of 7

SECTION 9: PHYSICAL – CHEMICAL PROPERTIES

Physical Description & colour: There is a range of colours for this product range.

Odour: Characteristic odour.

Boiling Point: >200

Freezing/Melting Point: No specific data. Liquid at normal temperatures.

Volatiles: No specific data. Expected to be low at 100°C.

Vapour Pressure: No data.

Vapour Density: No data.

Specific Gravity: 1.05-1.09 at 20°C

Water Solubility: Insoluble.

pH: No data.

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: No data.

Coeff Oil/water Distribution: No data

Viscosity: Thixotropic.

Autoignition temp: No data.

SECTION 10: STABILITY and REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated.

Incompatibilities: water, acids, bases, oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product may undergo polymerisation when heated. Polymerisation is often accompanied by liberation of heat, and may lead to a dangerous or explosive situation. If the product is seen to be heating up, treat as a fire incident.

SECTION 11: TOXICOLOGICAL INFORMATION

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient

Risk Phrases

2-propenoic Acid, 2-cyano-, Ethyl Ester

Conc>=10%: Xi; R36/37/38



Address: Unit 5/200 Hamilton Road New Gisborne VIC.
Postal: PO Box 98 Gisborne VIC 3437
Facsimile: 03 5428 4988
M.S.D.S INFORMATION: Telephone: 03 5428 3988

MATERIAL SAFETY DATA SHEET

PRODUCT: Cyberbond 2610

REVISED DATE: 01/06/2016
PAGE: 6 of 7

SECTION 12: ECOLOGICAL INFORMATION

Insufficient data to be sure of status.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

SECTION 14: TRANSPORT INFORMATION

ADG Code: This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

SECTION 15: REGULATORY INFORMATION

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: 2-Propenoic acid, 2-cyano-, ethyl ester, is mentioned in the SUSMP.

SECTION 16: OTHER INFORMATION

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS: Australian Inventory of Chemical Substances

SWA: Safe Work Australia, formerly ASCC and NOHSC

CAS number: Chemical Abstracts Service Registry Number

Hazchem Code: Emergency action code of numbers and letters that provide information to emergency services especially firefighters

IARC: International Agency for Research on Cancer

NOS: Not otherwise specified

NTP: National Toxicology Program (USA)

R-Phrase: Risk Phrase

SUSMP: Standard for the Uniform Scheduling of Medicines & Poisons

UN Number: United Nations Number



Address: Unit 5/200 Hamilton Road New Gisborne VIC.
 Postal: PO Box 98 Gisborne VIC 3437
 Facsimile: 03 5428 4988
 M.S.D.S INFORMATION: Telephone: 03 5428 3988

MATERIAL SAFETY DATA SHEET

PRODUCT: Cyberbond 2610 **REVISED DATE:** 01/06/2016
PAGE: 7 of 7

SECTION 16: OTHER INFORMATION

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

Emergency Contact: Poisons Information Centre 13 11 26
 Trimfix Supplies (03) 54283988

Disclaimer

Data provided is to best of Trimfix Supplies knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. Trimfix Supplies cannot anticipate or control the conditions under which this information may be used. Therefore, it is user’s responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document