

# TRIMFIX SUPPLIES

Trimfix Supplies: 200 Hamilton Road New Gisborne VIC.

Postal: PO Box 98 Gisborne VIC 3437

M.S.D.S INFORMATION – Telephone: 03 5428 3988

Facsimile: 03 5428 4988

## MATERIAL SAFETY DATA SHEET

**PRODUCT:** CLEAR TEXTURE FINISH

**ISSUED:** 01/06/2016

**PAGE:** 1 of 4

**Hazardous according to criteria of Worksafe Australia**

**UN No.** : 1263 **POISON SCHEDULE No.** :  
**HAZCHEM** : 3(Y)E  
**D.G. CLASS** : 3  
**SUB RISK** : None allocated

## PRODUCT IDENTIFICATION

**CORRECT SHIPPING NAME** : Paint  
**TRADENAMES** : Clear Texture Finish

## PHYSICAL DESCRIPTION / PROPERTIES

**APPEARANCE** : Varies in colour, medium to dark gray – strong solvent  
**FLASH POINT** : -4 C  
**BOILING RANGE** : 133 deg F  
**FLAMMABILITY LIMITS:** Upper: 11.5% Lower: 1.2%  
**VAPOUR DENSITY** : Heavier than air  
**SPECIFIC GRAVITY** : 0.90  
**SOLUBILITY IN WATER:** Stable  
**COATING V.O.C.** : 5.09 lb/gl  
**MATERIAL V.O.C.** : 5.09 lb/gl  
**EVAPORATION RATE** : Faster than n-BUTYL ACETATE

## INGREDIENTS

**CHEMICAL NAME:**

\*TOLUENE

\*METHYL ETHYL KETONE

\*ACETONE

## VAPOUR PRESSURE

**CAS No:**

**mm Hg @ TEMP**

**PROPORTION:**

108-88-3

22 68

50-55%

78-93-3

70 68

10-15%

67-64-1

186 68

5-10%

# TRIMFIX SUPPLIES

GLYCOL ETHER EP (ETHYLENE GLYCOL MONOPROPYL ETHER)

2807-30-9

1.3

68

5-10%

## MATERIAL SAFETY DATA SHEET

**PRODUCT:** CLEAR TEXTURE FINISH

**ISSUED:** 01/06/2016

**PAGE:** 2 of 4

## HEALTH HAZARD INFORMATION

### ACUTE EFFECTS – HEALTH RISKS & SYMPTOMS OF EXPOSURE

#### **INHALATION**

Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness and asphyxiation

#### **SKIN AND EYE CONTACT**

Moderate irritation, redness, blurred vision

#### **SKIN ABSORPTION**

Moderate irritation, redness, dermatitis

#### **INGESTION**

Gastrointestinal irritation, vomiting, diarrhea

#### **MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Bronchitis, CNS Disorders, allergies, nausea

#### **OTHER PRECAUTIONS:**

Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

#### **FIRST AID PROCEDURES:**

Eyes: Flush with large amounts of water lifting upper and lower lids, get medical attention.

Skin: Thoroughly wash exposed area with soap and water.

Inhalation: Remove to fresh air, give artificial respiration if necessary.

Ingestion: Keep person warm and quiet, seek medical advice regarding induction of vomiting.

## PRECAUTION FOR USE

**PERSONAL PROTECTION:** Avoid all contact with eyes, skin and inhaling the vapour. The use of barrier cream is beneficial

Skin: The wearing of PVC Nitrile or Neoprene gloves complying with AS 2161 is recommended

Eye Protection: Where splashing or spray mist is likely to occur, the wearing of Safety Glasses Complying with AS 1337 is recommended.

Inhalation: The wearing of an Organic Vapour – Particulate Respirator Type A Class 2 – P 1) complying with AS 1715/6 is recommended when spraying or if ventilation is inadequate.

# TRIMFIX SUPPLIES

## MATERIAL SAFETY DATA SHEET

**PRODUCT:** Clear Texture Finish

**ISSUED:** 01/06/2016

**PAGE** 3 of 4

### PRECAUTION FOR USE

#### ENGINEERING CONTROLS:

**Ventilation:** The working area must be adequately ventilated to maintain are concentrations below the exposure limits. If risk or overexposure exists, use with local exhaust ventilation or while wearing a vapour respirator. Product vapour is heavier than air and will collect at low level

ls. Hence, ventilate by extraction at low levels. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flame proof exhaust ventilation system is required.

For further information concerning ventilation, refer to:

AS 1940 – The storage and handling of flammable and combustible liquids &

AS 2430 – Explosive gas atmospheres.

Product is Highly Flammable. Isolate from sources of heat, naked flames, sparks and strong oxidising materials. Take precautions against static electricity discharges. Earth and bond all process equipment including tanks or drums. Ensure adequate ventilation to prevent and explosive vapour-air mixture. Vapours will travel considerable distances to sources of ignition.

#### STORAGE AND TRANSPORT :

Store in a cool, well ventilated area, away from ignition sources, heat, strong oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Take precautions against static electricity discharges.

Classified as a Dangerous Good Class 3 Flammable Liquid according to the Australian Code for the Transport of Dnagerous Goods by Road and Rail, Pkg Grp II

#### SPILLS AND DISPOSAL :

Remove all sources of ignition. Allow volatile portion to evaporate completely. Avoid breathing vapour. Use sand or earth to absorb spillage. Prevent contamination to waterways and sewerage.

# TRIMFIX SUPPLIES

## MATERIAL SAFETY DATA SHEET

**PRODUCT:** Clear Texture Finish

**ISSUED:** 01/06/2016

**PAGE** 4 of 4

Data last modified: 01/06/2016

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information provided is to the best of Trimfix Supplies' knowledge and is believed to be accurate and reliable as of the date indicated. However, Trimfix Supplies does not make or give any warranty or guarantee whatsoever, with respect to the information's accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. Hence the user undertakes not to hold Trimfix Supplies liable or responsible in any way whatsoever in relation or consequential to such use.